



SPECIFICATION & SUBMITTAL SHEET

LINESET BOX™

Line set rough-in box for the exterior wall

MADE IN THE USAJ.T. Products LLC
since 1999

One molded box at the exterior wall penetration. The line set, condensation drain and low voltage wire terminate in one clean, weathertight point, protected from rough-in until the condenser is set.

ORDER

White Amazon ASIN B0127QD340

Black Amazon ASIN B0127QD39E

Distributors jtproducts.com/locator.html**SPECIFICATIONS**

Rough opening	5-3/4 × 10-3/4 in, cut in the wall sheathing
Mounting flange	12.16 × 7.18 in, 8 pre-drilled 1/8 in holes
Body through the wall	10.63 × 5.65 in, 3.60 in deep behind the flange
Overall depth	4.45 in including the 0.75 in front lip
Orientation	Tapered end at the bottom; holes are sawn in the flat top
Carries	Line set, condensation drain, low voltage wire
Line set pass-through	Hole-saw on site: 1-7/8 in for a 7/8 × 3/8 line set

Drain pass-through	Hole-saw on site: 1 in for 3/4 in Schedule 40 PVC
Fasteners	8 × 3/4 in galvanized deck screws or equal, not included
Material	UL-recognized polypropylene, UL 94 HB, UL File E130336
Colors	White or black, same box
Weight	10.45 oz
When to install	Rough-in, before siding or exterior finish
Made in	USA · Patent pending

Installation guide: jtproducts.com/Lineset-Box-Installation-Guide.pdf**SUBMITTAL**

Project _____
Contractor _____
Submitted by _____
Spec section _____

Location _____
Engineer / architect _____
Date _____
Quantity _____

☐ Approved ☐ Approved as noted ☐ Revise and resubmit

Reviewer / date: _____